

# Preliminary

## GaN Microwave Generator

### RIU243K0-40TG



#### Product Features

- 2400 ~ 2500MHz
- High Output power: 3kW (CW) Peak Power
- Using GaN on SiC HEMT
- 58% System Efficiency
- Excellent Reliability
- Output Power Adjustable from 0.03 to 3kW
- Excellent Frequency Spectrum at Low Power

#### Applications

- Building Block for High-Power Systems
- Plasma Generation
- Industrial Heating and Drying
- CVD Equipment Sterilization



#### Description

RIU243K0-40TG is a 3kW, GaN solid-state microwave generator designed ideally for microwave heating and plasma generation applications. The RIU243K0-40TG provides continuous wave (CW) and or pulse output power adjustable from 30W to 3000W at frequencies ranging between 2400MHz and 2500MHz. The RIU243K0-40TG is a remote-type microwave generator system with the SSPA head and power supply unit separately, providing greater system flexibility. The RIU243K0-40TG comes equipped with a 3kW SSPA head, a Window-based GUI, and a PLL Synthesizer/Control Module

#### Electrical Specifications

PARAMETER		UNIT	MIN	TYP	MAX	SYMBOL
Operating Frequency	Adjustable Range	MHz	2400	-	2500	F <sub>o</sub>
	Step Size	kHz	500	-	-	
Output Power	Adjustable Range	kW	0.03	-	3	P <sub>o</sub>
	Step Size	kW	0.01	-	-	
Operating Mode		CW				
Power Spectrum Bandwidth**		KHz	-	-	500	S <sub>b</sub>
Frequency Accuracy & Stability		ppm	-2.5	-	2.5	F <sub>s</sub>
Efficiency (DC to RF)		%	-		58	Eff
Phase Shift	Operating Range	Deg	0		180	
	Step Size	Deg	-	1.0	-	
Operating Voltage	PSU	V	380		415	VAC
	SSPA Head			50		VDC
Control Interface		RS-422				

# Preliminary

## GaN Microwave Generator

### RIU243K0-40TG



## Generator Alarm & Protection Features

PARAMETER	State	CONDITION
Forward Power	Alarm	Output Power > 3kW
Over-Temperature	Alarm	System Temperature > 50 C°
Reflected Power	Alarm	750W ~ 1.5 kW
PLL Unlock <sup>(1)</sup>	Disabled	System
Forward Power	Disabled	Output Power > 3.3kW
Over-Temperature	Disabled	System Temperature > 55 C°
Reflected Power	Disabled	Reflected Power > 1.5kW

\*Remarks

(1) PLL Unlock definition

## SSPA Head Mechanical Specifications

PARAMETER	UNIT	VALUE
Dimensions (W x D x H)	mm	305 x 205 x 515.5
SSPA Head Weight	Kg	31
Microwave Output Port	-	WR340
DC & GND	-	Circular Connector 4pin (Female)
I/O Connector		D-Sub 9-Pin
Cooling Requirements	-	Water Cooling Rate 10L/Min, 5Bar
		Cooling Water Inlet Temperature 20 °C (typ.)
		Relative humidity below dew point (non-condensing)
		* De-ionized water shall be used to prevent system damage Antifreeze water is recommended below 0°C environmental conditions
Fluid Inlet/Outlet Size	Inch	G 3/8

Remarks: Dimensions and Connectors may be subject to change.

\*Product warranty applies ONLY to products operated within the normal and specified operations

## Environmental Specifications


PARAMETER	UNIT	VALUE
Operating Case Temperature <sup>(1)</sup>	°C	15 ~ 50
Environmental/Storage Temperature	°C	10 ~ 40

Remarks: (1) Operating case temperature is the temperature detected at the PA temp sensor.

**Preliminary**  
**GaN Microwave Generator**  
**RIU243K0-40TG**



**SSPA Head Appearance**



Preliminary

GaN Microwave Generator

RIU243K0-40TG



Power Supply Unit Specifications (DMPS-9KW)

PARAMETER	UNIT	VALUE
Input Voltage	VAC	3Ø4W400 ±10%
Frequency	Hz	45-66
Power Factor	%	98 ≥ Typ.
PSU Efficiency	%	96
Output Voltage	VDC	50
Output Current	A	180 max.
Weight	Kg	17
Dimensions (W x D x H)	mm	482 x 444.7 x 88.9
Cooling	-	Air Cooling


PSU Image



**Preliminary**  
**GaN Microwave Generator**  
**RIU243K0-40TG**



**Microwave Generator Setup and Interface Concept**



**Preliminary**  
**GaN Microwave Generator**  
**RIU243K0-40TG**



**Revision History**

Part Number	Release Date	Version	Description	Data Sheet Status
RIU243K0-40TG	December, 2022	0.1	Initial release of datasheet	
RIU243K0-40TG	May, 2023	0.2	Modification of Inlet/Outlet size	



**Certification**

This product is manufactured by a company that is certified for the AS9100D quality management system.

RFHIC Corporation reserves the right to make changes to any products herein or to discontinue any product at any time without notice. While product specifications have been thoroughly examined for reliability, RFHIC Corporation strongly recommends buyers to verify that the information they are using is accurate before ordering. RFHIC Corporation does not assume any liability for the suitability of its products for any particular purpose, and disclaims any and all liability, including without limitation consequential or incidental damages. RFHIC products are not intended for use in life support equipment or application where malfunction of the product can be expected to result in personal injury or death. Buyer uses or sells such products for any such unintended or unauthorized application, buyer shall indemnify, protect, and hold RFHIC Corporation and its directors, officers, stockholders, employees, representatives, and distributors harmless against any and all claims arising out of such unauthorized use. All sales inquiries and support should be directed to the local authorized geographic distributor for RFHIC Corporation. For customers in the US, please contact the US sales team through our website at <https://rfhic.com/rfhic-us/>. For all other inquiries, please contact our international sales team through our website portal at <https://rfhic.com/contact/>.